

# Power Optimizer

## For Europe

P650 / P701 / P730 / P800p / P801 / P850 / P950 / P1100

POWEROPTIMIZER



## PV power optimization at the module level

The most cost-effective solution for commercial and large field installations

- Specifically designed to work with SolarEdge inverters
- Up to 25% more energy
- Superior efficiency (99.5%)
- Balance of System cost reduction; 50% less cables, fuses and combiner boxes, over 2x longer string lengths possible
- Fast installation with a single bolt
- Advanced maintenance with module-level monitoring
- Module-level voltage shutdown for installer and firefighter safety
- Use with up to two PV modules connected in series or in parallel

# Power Optimizer

## For Europe

P650 / P701 / P730

| Power Optimizer Model<br>(Typical Module Compatibility)   | P650<br>(for up to 2 x 60-cell<br>PV modules)   | P701<br>(for up to 2 x 60/120-cell<br>PV modules) | P730<br>(for up to 2 x 72-cell PV<br>modules) |            |
|---|---|---|---|------------|
| <b>INPUT</b>  |   |   |   |            |
| Rated Input DC Power <sup>(1)</sup>   | 650   | 730   | 760   | W          |
| Connection Method   | Single input for series connected modules       |   |   |            |
| Absolute Maximum Input Voltage (Voc at lowest temperature)  | 96  |   | 125   | Vdc        |
| MPPT Operating Range  | 12.5 - 80                                       |   | 12.5 - 105                                    | Vdc        |
| Maximum Short Circuit Current per Input (Isc)   | 11  | 11.75   | 11.75*  | Adc        |
| Maximum Efficiency  | 99.5  |   |   | %          |
| Weighted Efficiency   | 98.6  |   |   | %          |
| Overvoltage Category  | II  |   |   |            |
| <b>OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING SOLAREEDGE INVERTER)</b>                     |   |   |   |            |
| Maximum Output Current  | 15  |   |   | Adc        |
| Maximum Output Voltage  | 80  |   |   | Vdc        |
| <b>OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM SOLAREEDGE INVERTER OR SOLAREEDGE INVERTER OFF)</b> |   |   |   |            |
| Safety Output Voltage per Power Optimizer   | 1 ± 0.1   |   |   | Vdc        |
| <b>STANDARD COMPLIANCE</b>  |   |   |   |            |
| EMC   | FCC Part 15 Class B, IEC61000-6-2, IEC61000-6-3 |   |   |            |
| Safety  | IEC62109-1 (class II safety)                    |   |   |            |
| RoHS  | Yes   |   |   |            |
| Fire Safety   | VDE-AR-E 2100-712:2013-05                       |   |   |            |
| <b>INSTALLATION SPECIFICATIONS</b>  |   |   |   |            |
| Compatible SolarEdge Inverters  | Three phase inverters<br>SE15K & larger         | Three phase inverters SE16K & larger              |   |            |
| Maximum Allowed System Voltage  | 1000  |   |   | Vdc        |
| Dimensions (W x L x H)  | 129 x 153 x 42.5 / 5.1 x 6 x 1.7                |   | 129 x 153 x 49.5 / 5.1 x 6 x 1.9              | mm<br>/ in |
| Weight  | 834 / 1.8                                       |   | 933 / 2.1                                     | gr / lb    |
| Input Connector   | MC4 <sup>(2)</sup>                              |   |   |            |
| Input Wire Length   | 0.16 / 0.52                                     |   | 0.16 / 0.52 , 0.9 / 2.95 <sup>(3)</sup>       | m / ft     |
| Output Connector  | MC4   |   |   |            |
| Output Wire Length  | Portrait Orientation: 1.2 / 3.9                 |   |   | m / ft     |
|   | Landscape Orientation: 1.8 / 5.9                |   | Landscape Orientation: 2.2 / 7.2              |            |
| Operating Temperature Range <sup>(4)</sup>  | -40 to +85 / -40 to +185                        |   |   | °C / °F    |
| Protection Rating   | IP68 / NEMA6P                                   |   |   |            |
| Relative Humidity   | 0 - 100   |   |   | %          |

\* For P730 with manufactured date older than working week 6 of 2020 the Isc is 11A. The manufacture code is indicated in the power optimizer's serial number.

Example: S/N SJ0620A-xxxxxxx (working week 06 in 2020)

(1) Rated power of the module at STC will not exceed the power optimizer "Rated Input DC Power". Modules with up to +5% power tolerance are allowed

(2) For other connector types please contact SolarEdge

(3) Longer inputs wire length are available for use with split junction box modules. (For 0.9m/2.95ft order P730-xxxLxxx)

(4) For ambient temperature above +70°C / +158°F power de-rating is applied. Refer to Power Optimizers Temperature De-Rating Technical Note for more details

# Power Optimizer

## For Europe

P800p / P801 / P850 / P950 / P1100

| Power Optimizer Model<br>(Typical Module Compatibility)   | P800p<br>(for up to 2 x<br>96-cell 5" PV<br>modules)  | P801<br>(for up to 2 x<br>72/144-cell<br>PVmodules) | P850<br>(for up to 2 x<br>high power or bi-<br>facial modules) | P950<br>(for up to 2 x high<br>power or bi-<br>facial modules) | P1100<br>(for up to 2 x<br>high power or bi-<br>facial modules) |            |
|---|---|---|--|--|---|------------|
| <b>INPUT</b>  |   |   |  |  |   |            |
| Rated Input DC Power <sup>(1)</sup>   | 800   | 800   | 850  | 950  | 1100  | W          |
| Connection Method   | Dual input for independently connected <sup>(7)</sup> |   | Single input for series connected modules                      |  |   |            |
| Absolute Maximum Input Voltage (Voc at lowest temperature)  | 83  |   | 125  |  |   | Vdc        |
| MPPT Operating Range  | 12.5 - 83   |   | 12.5 - 105   |  |   | Vdc        |
| Maximum Short-Circuit Current per Input (Isc)   | 7   | 11.75   | 12.5   |  | 14  | Adc        |
| Maximum Efficiency  |   |   |  | 99.5   |   | %          |
| Weighted Efficiency   |   |   |  | 98.6   |   | %          |
| Overvoltage Category  |   |   |  | II   |   |            |
| <b>OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING SOLAREEDGE INVERTER)</b>                     |   |   |  |  |   |            |
| Maximum Output Current  | 18  | 15  | 18   |  |   | Adc        |
| Maximum Output Voltage  |   |   |  | 80   |   | Vdc        |
| <b>OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM SOLAREEDGE INVERTER OR SOLAREEDGE INVERTER OFF)</b> |   |   |  |  |   |            |
| Safety Output Voltage per Power Optimizer   |   |   |  | 1 ± 0.1  |   | Vdc        |
| <b>STANDARD COMPLIANCE</b>  |   |   |  |  |   |            |
| EMC   | FCC Part 15 Class B, IEC61000-6-2, IEC61000-6-3       |   |  |  |   |            |
| Safety  | IEC62109-1 (class II safety)                          |   |  |  |   |            |
| RoHS  | Yes   |   |  |  |   |            |
| Fire Safety   | VDE-AR-E 2100-712:2013-05                             |   |  |  |   |            |
| <b>INSTALLATION SPECIFICATIONS</b>  |   |   |  |  |   |            |
| Compatible SolarEdge Inverters  | Three phase inverters SE16K & larger                  |   |  |  | Three phase inverters SE25K & larger                            |            |
| Maximum Allowed System Voltage  | 1000  |   |  |  |   | Vdc        |
| Dimensions (W x L x H)  | 129 x 168 x 59 /<br>5.1 x 6.61 x 2.32                 | 129 x 153 x 49.5 /<br>5.1 x 6 x 1.9                 | 129 x 162 x 59 / 5.1 x 6.4 x 2.32                              |  |   | mm<br>/ in |
| Weight  | 1064 / 2.3  | 933 / 2.1   | 1064 / 2.3   |  |   | gr / lb    |
| Input Connector   | MC4 <sup>(2)</sup>                                    |   |  |  |   |            |
| Input Wire Length   | 0.16 / 0.52   | 0.16 / 0.52, 0.9 / 2.95                             | 0.16 / 0.52, 0.9 / 2.95, 1.3 / 4.26, 1.6 / 5.24 <sup>(3)</sup> | 0.16 / 0.52, 1.3 / 4.26, 1.6 / 5.24 <sup>(3)</sup>             | 0.16 / 0.52, 1.3 / 4.26 <sup>(3)</sup>                          | m / ft     |
| Output Connector  | MC4   |   |  |  |   |            |
| Output Wire Length  | Portrait Orientation: 1.2 / 3.9                       |   |  |  | 2.4 / 7.8   | m / ft     |
|   | Landscape Orientation: 1.8 / 5.9                      | Landscape Orientation: 2.2 / 7.2                    |  |  |   |            |
| Operating Temperature Range <sup>(4)</sup>  | -40 to +85 / -40 to +185                              |   |  |  |   | °C / °F    |
| Protection Rating   | IP68 / NEMA6P   |   |  |  |   |            |
| Relative Humidity   | 0 - 100   |   |  |  |   | %          |

(1) Rated power of the module at STC will not exceed the power optimizer "Rated Input DC Power". Modules with up to +5% power tolerance are allowed

(2) For other connector types please contact SolarEdge

(3) Longer inputs wire length are available for use with split junction box modules. (For 0.9m/ 2.95ft order P801/P850-xxxLxxx. For 1.3m/2.95ft order P850/P950/P1100-xxxXxxx. For 1.6m/5.24ft order P850/P950-xxxYxxx)

(4) For ambient temperature above +70°C / +158°F power de-rating is applied. Refer to Power Optimizers Temperature De-Rating Technical Note for more details

| PV System Design Using a SolarEdge Inverter <sup>(5)(6)(7)(8)</sup> |                  | 230/400V Grid SE15K and larger |      |      | 230/400V Grid SE16K and larger |                      |      |       | 230/400V Grid SE25K and larger |      | 277/480V Grid SE33.3K and larger |                       |                |      |       |
|---|------------------|--------------------------------|------|------|--------------------------------|----------------------|------|-------|--------------------------------|------|----------------------------------|-----------------------|----------------|------|-------|
|   |                  | P650                           | P701 | P730 | P801                           | P800p/<br>P850       | P950 | P1100 | P650                           | P701 | P730                             | P801                  | P800p/<br>P850 | P950 | P1100 |
| Compatible Power Optimizers   |                  | P650                           | P701 | P730 | P801                           | P800p/<br>P850       | P950 | P1100 | P650                           | P701 | P730                             | P801                  | P800p/<br>P850 | P950 | P1100 |
| Minimum String Length   | Power Optimizers | 14                             |      |      |                                |                      |      |       |                                |      |                                  |                       |                |      |       |
|   | PV Modules       | 27                             |      |      |                                |                      | 27   |       |                                |      |                                  | 27                    |                |      |       |
| Maximum String Length   | Power Optimizers | 30                             |      |      |                                |                      |      |       |                                |      |                                  |                       |                |      |       |
|   | PV Modules       | 60                             |      |      |                                |                      | 60   |       |                                |      |                                  | 60                    |                |      |       |
| Maximum Nominal Power per String                                    |                  | 11250 <sup>(9)</sup>           |      |      |                                | 13500 <sup>(9)</sup> |      |       | 12750 <sup>(10)</sup>          |      |                                  | 15300 <sup>(10)</sup> |                | W    |       |
| Parallel Strings of Different Lengths or Orientations               |                  | Yes                            |      |      |                                |                      |      |       |                                |      |                                  |                       |                |      |       |

(5) P650/P701/P730/P801 can be mixed in one string, and P850/P800p/P950/P1100 can also be mixed in one string. It is not allowed to mix P650/P701/P730/P801 with P850/P800p/P950/P1100, nor is it allowed to mix P650-P1100 with P370-P505 in one string

(6) In a case of odd number of PV modules in one string it is allowed to install one P650/P701/P730/P850/P800p/P801/P950/P1100 power optimizer connected to one PV module. When connecting a single module to the P800p seal the unused input connectors with the supplied pair of seals

(7) Power optimizers intended for use with two PV modules each (2:1 connection), can be used with a single PV module (1:1 connection), as long as the entire string uses 1:1 connections

(8) For SE15k and above, the minimum DC power should be 11KW







(9) For the 230/400V grid: With P650/P701/P730/P801 up to 13,500W per string may be installed, with P850/P800p up to 17,500W and with P950/P1100 up to 18,500W per string may be installed when the maximum power difference between each string is 2,000W. For P950/P1100, minimum two string are required for SE16K-SE27.6K inverters, and for SE30K and above minimum three string are required

(10) For the 277/480V grid: With 650/P701/P730/P801 up to 15,000W per string may be installed, with P850/P800p up to 17,500W and with P950/P1100 up to 20,300W per string may be installed when the maximum power difference between each string is 2,000W. For P950/P1100, minimum three string are required for SE33.3K and SE40K inverters

SolarEdge is a global leader in smart energy technology. By leveraging world-class engineering capabilities and with a relentless focus on innovation, SolarEdge creates smart energy solutions that power our lives and drive future progress.

SolarEdge developed an intelligent inverter solution that changed the way power is harvested and managed in photovoltaic (PV) systems. The SolarEdge DC optimized inverter maximizes power generation while lowering the cost of energy produced by the PV system.

Continuing to advance smart energy, SolarEdge addresses a broad range of energy market segments through its PV, storage, EV charging, UPS, and grid services solutions.

-  SolarEdge
-  @SolarEdgePV
-  @SolarEdgePV
-  SolarEdgePV
-  SolarEdge
-  info@solaredge.com

[solaredge.com](https://www.solaredge.com)

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREEDGE, the SolarEdge logo, OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: 03/2021 DS-000024-1.0-EU. Subject to change without notice.

Cautionary Note Regarding Market Data and Industry Forecasts: This brochure may contain market data and industry forecasts from certain third-party sources. This information is based on industry surveys and the preparer's expertise in the industry and there can be no assurance that any such market data is accurate or that any such industry forecasts will be achieved. Although we have not independently verified the accuracy of such market data and industry forecasts, we believe that the market data is reliable and that the industry forecasts are reasonable.



**solar**edge